

UTILITY
PATENT APPLICATION
TRANSMITTAL

Attorney Docket No.

36J.P187

First Named Inventor or Application Identifier

Timothy L. Kohler

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)

2. ☒ Specification Total Pages **57**

3. ☒ Drawing(s) (35 USC 113) Total Sheets **10**

4. ☒ Oath or Declaration Total Pages **2**

a. ☒ Newly executed (original or copy)

b. ☐ Unexecuted for information purposes

c. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]

i. ☐ DELETION OF INVENTOR(S)
Signed Statement attached deleting
inventor(s) named in the prior application,
see 37 CFR 1.63(d)(2) and 1.33(b).

5. ☐ Incorporation By Reference (useable if Box 4c is checked)
The entire disclosure of the prior application, from which a copy
of the oath or declaration is supplied under Box 4c, is considered
as being part of the disclosure of the accompanying application
and is hereby incorporated by reference therein.

6. ☒ Microfiche Computer Program (Appendix)

7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)

a. ☐ Computer Readable Copy

b. ☐ Paper Copy (identical to computer copy)

c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))

9. ☐ 37 CFR 3.73(b) Statement ☒ Power of Attorney
(when there is an assignee)

10. ☐ English Translation Document (if applicable)

11. ☒ Information Disclosure Statement (IDS)/PTO-1449 ☒ Copies of IDS Citations

12. ☐ Preliminary Amendment

13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)

14. ☐ Small Entity ☐ Statement filed in prior
Statement(s) application
Status still proper and desired

15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)

16. ☐ Other: _____

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. ____/____

18. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label **05514** (Insert Customer No. or Attach bar code label here) or ☐ Correspondence address below

NAME

Address

City

State

Zip Code

Country

Telephone

Fax



CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS (37 CFR 1.16(c))	90-20 =	70	X \$ 18.00 =	\$ 1,260.00
	INDEPENDENT CLAIMS (37 cfr 1.16(b))	10-3 =	7	X \$ 78.00 =	\$ 546.00
	MULTIPLE DEPENDENT CLAIMS (if applicable) (37 CFR 1.16(d))			\$260.00 =	\$ ---
				BASIC FEE (37 CFR 1.16(a))	\$ 760.00
				Total of above Calculations =	\$ 2,566.00
	Reduction by 50% for filing by small entity (Note 37 CFR 1.9, 1.27, 1.28).				---
	TOTAL =				\$ 2,566.00

19. Small entity status


- a. ☐ A Small entity statement is enclosed
- b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
- c. ☐ Is no longer claimed.

20. ☒ A check in the amount of \$ 2,566.00 to cover the filing fee is enclosed.

21. ☒ A check in the amount of \$ 40.00 to cover the recordal fee is enclosed.

22. The Commissioner is hereby authorized to credit overpayments or charge the following fees to Deposit Account No. 06-1205:

- a. ☒ Fees required under 37 CFR 1.16.
- b. ☒ Fees required under 37 CFR 1.17.
- c. ☐ Fees required under 37 CFR 1.18.

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED	
NAME	Michael K. O'Neill, Reg. No. 32,622
SIGNATURE	
DATE	February 1, 1999

5
10
15
20

**APPLICATION PROGRAMMING INTERFACE
FOR MEASURING DEVICES**

BACKGROUND OF THE INVENTION

This application is being filed with a microfiche appendix of computer program listings consisting of one (1) fiche having fifty-one (51) frames.

A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent file or records, but otherwise reserves all copyright rights whatsoever.

Field Of The Invention

The present invention concerns an application programming interface (API) usable by a software developer when writing an application program, such as a color calibration program, that

uses a color measuring device. In particular, the present invention relates to an API that provides a common interface between such an application program and plural different types of color measuring devices.

Description Of The Related Art

One common use of color measuring devices is to calibrate color fidelity of color recording devices. Typically, the recording device (such as a color laser beam printer or ink jet printer) records color patches on a recording medium. The color values of the patches are measured by the color measuring device, the measured values are compared against expected (or ideal) values, and the comparisons are used to calibrate the recording device.

Color measuring devices come in many different physical structures, such as XY tables, strip readers, hand-held patch readers, and flatbed scanners, and operate in different ways using different numbers and types of sensors. Color patches are input in different ways to color measuring devices which have different physical structures. For example, patches are input to an XY table on a sheet that has an array of patches printed thereon, whereas patches are input to a strip reader on strips that each have one or more rows of patches printed thereon. The sensors that actually perform color measurements are positioned on patches in different ways depending on the physical structures of the color measuring devices.

In order to make accurate color measurements for use in calibrating a color recording device, the color measuring devices themselves must be calibrated properly. For example, for some color measuring devices to

position their sensor(s) accurately, the positioning mechanism in the color measuring devices must be calibrated. In addition, the sensors in some color measuring devices must be calibrated so as to ensure proper color measurements. Depending on the numbers and types of sensors as well as the physical structures of the color measuring devices, calibration of the position of the sensors and calibration of the sensors differ among different types of color measuring devices.

In addition, application programs that use color measuring devices should provide interfaces to the user. These interfaces should include instructions to the user at various points throughout operations performed using the color measuring devices. The timing and content of these instructions also differ among different color measuring devices.

As a result of the foregoing differences in operation among the different types of color measuring devices, a different command set is needed for each different type of device. Application programs that use the color measuring devices often must include different numbers of calls to commands in the different command sets in order to perform a same operation with different color measuring devices. In addition, the application programs often must include different interfaces for each different type of color measuring device. These different command sets and interfaces greatly complicate the task of writing application programs that perform color measurements. As a result, conventional application programs for performing color measurements must include separate and often lengthy routines for taking color measurements with each different type of supported device. In addition, once a conventional application program is

written, that application program cannot use new types of color measuring devices, because the new device would require calls to commands in a new command set.

5

SUMMARY OF THE INVENTION

Accordingly, there is a need for an application programming interface (API) that allows a software developer to write a single set of routines for taking color measurements using plural different types of color measuring devices.

The present invention addresses the foregoing need by providing an application programming interface that abstracts the operations needed to perform color measurements. An application program only needs to include calls to the functions in this API in order to use any supported type of color measuring device. The API in turn calls the necessary commands for performing color measurement operations.

In order to allow the application program to provide appropriate instructions during operations performed with a color measuring device, certain functions in the API are called numerous times in order to complete their respective operations. In order to enable the application program to call such a function a correct number of times, the API provides the application program with flow control data of the number of times that the function needs to be called so as to complete its operation with a particular color measuring device. The API also preferably provides the application program with display values for display so as to instruct the user in manipulating the color measuring device.

By virtue of the foregoing, the application program does not need to include separate routines

for each different type of supported color measuring device. Instead, the application program need only include calls to the functions in the API and include mechanisms for handling display values and flow control data provided by the API. Moreover, if the API is implemented in a dynamically linkable library (DLL), an existing application program that calls the functions in the API can use new types of color measuring devices by linking to an updated version of the DLL.

Accordingly, in one aspect the invention is an API that provides a common interface between an application program and plural different types of color measuring devices each having at least one color measuring sensor. The API includes plural functions for operating any of the plural different types of color measuring devices. In order to complete an operation performed by at least one of the plural functions, the function that performs the operation must be called a number of times which is different for at least two different types of color measuring devices. For a particular color measuring device, the API provides the application program with flow control data of the number of times that the function must be called. This flow control data preferably can be provided by the function, in the form of a call-again value or as a numerical value, or by a separate function in the API such as a get-device-capabilities function. In some embodiments of the invention, a combination of these methods of providing the flow control data is utilized.

Preferably, the functions in the API also provide the application program with display values which are different for at least two different types of color measuring devices. The display values are for display to a user, preferably by the application

program, so as to instruct the user in manipulating the color measuring device that is being operated.

In another aspect, the invention is an API that provides a common interface between an application program and plural different types of color measuring devices each having at least one color measuring sensor. The API includes plural functions for operating any of the plural different types of color measuring devices. The plural functions include a calibrate-position function, a calibrate-sensor function, a move-to-patch function, and a make-measurement function.

The calibrate-position function calibrates a relative position of a recording medium with respect to any of the plural different types of color measuring devices. Preferably, the calibrate-position function provides the application program with at least one display value that is to be displayed so as to instruct a user to position the recording medium or to position any of the color measuring sensors.

The calibrate-sensor function calibrates any of the color measuring sensors of any of the plural different types of color measuring devices. Preferably, the calibrate-sensor function provides the application program with at least one display value that is to be displayed so as to instruct the user in calibrating the sensor.

The move-to-patch function relatively positions any of the color measuring sensors and a color patch for any of the plural different types of color measuring devices. The move-to-patch function is provided with a logical color patch number by the application program. In order to relatively position the color patch and any of the color measuring sensors for some color measuring devices, the move-to-patch function preferably can provide

the application program with a display value which instructs the user to manipulate the color measuring devices or to move the recording medium. In order to relatively position the color patch and any of the color measuring sensors for other color measuring devices, the move-to-patch function preferably causes the color measuring device to move the recording medium or to move the color measuring sensors. In any case, the move-to-patch function preferably provides the application program with a recalibrate value in a case that the relative position of the recording medium needs to be recalibrated, for example when a new recording medium is loaded into the color measuring device.

The make-measurement function makes a color measurement of the patch at which any of the color measuring sensors is relatively positioned, and the make-measurement function provides the application program with a color measurement value for the color patch. The make-measurement function preferably provides the application program with at least one display value that is to be displayed so as to instruct the user in making the color measurement. In addition, the make-measurement function preferably provides the application program with a recalibrate value in a case that any of the color measuring sensors needs to be recalibrated.

In order to complete an operation performed by at least one of the plural functions, the function that performs the operation must be called a number of times which is different for at least two different types of color measuring devices. For a color measuring device that is being operated, the API provides the application program with flow control data of the number of times that the function must be called. The flow control data preferably can be provided by the function, either

in the form of a call-again value or a numerical value, or by a get-device-capabilities function included in the API.

5 The computer-executable process steps for the functions in the API preferably are stored in a dynamically linkable library (DLL). Thus, updated API functions can be used by an application program to access new types of measuring devices simply by linking the application program to the DLL.

10 The API according to the invention relieves application programs from the burden of having to include separate routines for taking color measurements with each different type of supported color measuring device. Instead, in order to take
15 color measurements with any type of supported color measuring device, the application program need only include calls to functions in the API. The API itself handles the different interfaces to the different types of color measuring devices. As a
20 result, the application program is far simpler to write.

 This brief summary has been provided so that the nature of the invention may be understood quickly. A more complete understanding of the
25 invention can be obtained by reference to the following detailed description of the preferred embodiments thereof in connection with the attached drawings.

30 BRIEF DESCRIPTION OF THE DRAWINGS

 Figure 1 is a representational view of a computer system in which color fidelity of a color printer is calibrated using a color measuring device.

35 Figure 2 is a detailed block diagram showing the internal architecture of the computer system shown in Figure 1.

Figure 3 is a block diagram for explaining a system for calibration of color fidelity of a color printer by a color calibration program according to the invention.

5 Figure 4 is a block diagram for explaining a structure of a measuring device application programming interface (API) according to the invention.

10 Figure 5 is a representational view of a development system for development of an application program using a measuring device API according to the invention.

15 Figure 6 is a detailed block diagram showing the internal architecture of the development system shown in Figure 5.

20 Figures 7A to 7C are flowcharts for explaining color calibration by a color calibration program using a measuring device API according to the invention.

25 Figure 8 is a block diagram for explaining a variation of the structure of the measuring device API according to the invention.

30 Figure 9 is a block diagram for explaining another variation of the structure of the measuring device API according to the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

35 Figure 1 is a representational view of a computer system in which color fidelity of a color printer is calibrated using a color measuring device. Shown in Figure 1 are color printer 1 and computer system 6, together with a variety of color measuring devices, such as XY table 2, strip reader 3, hand-held patch reader 4, and scanner 5.

 Color printer 1 is depicted in Figure 1 as an ink jet printer. However, any printer capable of printing color images on recording media can be

utilized by a color calibration program written according to the invention, such as ink jet printers and laser printers. Color printer 1 prints color images in response to print jobs received from computer system 6 over printer interface 8.

Measuring device 10 is a color measuring device that is used to generate color measurements of color patches input thereto. The color measurements generated by color measuring device 10 are transmitted over measuring device interface 9 to computer system 6. Examples of measuring device 10 include XY table 2, strip reader 3, and hand-held patch reader 4 for reading individual color patches.

Color patches are input to each of the different types of color measuring devices in different ways. For example, patches are input to XY table 2 on a sheet that has an array of patches printed thereon, whereas patches are input to strip reader 3 on strips that each have one or more rows of patches printed thereon. The sensors that actually perform color measurements are positioned on patches in different ways depending on the physical structures of the color measuring devices. For example, XY table 2 typically includes motors and gimbals for automatically positioning the sensors, while hand-held patch reader 4 typically must be manually positioned over a patch.

Flatbed scanner 5 can also serve as a color measuring device, provided that scanner 5 is properly calibrated. Color patches are input to flatbed scanner 5 in a similar manner as the patches are input to XY table 2, namely on a sheet that has an array of patches printed thereon.

The different color measuring devices also can use entirely different types and arrangements of sensors for making the color measurements. For example, color measuring device 10 can be a

spectrometer (i.e., a spectrophotometer or a spectroradiometer), which uses sensors that preferably measure light intensity for frequencies across the entire visible spectrum. Alternatively, color measuring device 10 can be a colorimeter or densitometer, which uses sensors that measure light intensity for XYZ or RGB components of the spectrum.

In any case, each of the color measuring devices have at least one color sensor for making color measurements. In order to ensure accurate color measurements, the sensor(s) should be calibrated. In addition, depending on the type of measuring device 10, a relative position of a recording medium with respect to the device might have to be calibrated. In particular, each time a new recording medium (e.g., strip or sheet) is input to color measuring device 10, the position of the recording medium should be recalibrated so that the color measuring device can properly locate color patches printed thereon.

Because of the different ways that color patches are input and measured by the different types of color measuring devices, a different command set is needed to calibrate and to make color measurements with each different type of color measuring device.

As shown in Figure 1, computer system 6 is connected to printer 1 through printer interface 8 and measuring device 10 through measuring device interface 9. Provided with computer system 6 are display 12 which may be a color monitor, keyboard 14 for entering user commands, and pointing device 15 such as a mouse for pointing to and for manipulating graphical user interfaces and other objects displayed on display 12.

Computer system 6 also includes a mass storage device such as fixed disk 16. This mass

storage device is for storing computer-executable process steps for a color calibration program and a measuring device DLL according to the invention, as well other application programs and an operating system including a printer driver and a measuring device driver. Such storage may also be provided by a CD-ROM (not shown).

It should be understood that, although a programmable general-purpose computer is shown in Figure 1, a dedicated computer terminal or other type of data processing equipment can utilize the present invention.

Figure 2 is a detailed block diagram showing the internal architecture of computer system 6. As shown in Figure 2, computer system 6 includes central processing unit 23 which interfaces with computer bus 24. Also interfacing with computer bus 24 are fixed disk 16, main memory (RAM) 26, read only memory (ROM) 27, floppy disk interface 29, display interface 30 to display 12 (not shown), keyboard interface 32 to keyboard 14 (not shown), pointing device interface 33 to pointing device 15 (not shown), printer interface 8 to color printer 1, and measuring device interface 9 to measuring device 10.

Main memory 26 interfaces with computer bus 24 so as to provide RAM storage to CPU 23 during execution of software applications. More specifically, CPU 23 loads process steps from fixed disk 16, another storage device, or some other source such as a network (not shown), into main memory 26. CPU 23 then executes the stored process steps from main memory 26 in order to execute application programs. Data such as print data and color measurement data can be stored in main memory 26, where the data can be accessed by CPU 23 during execution of the process steps.

As shown in Figure 2, fixed disk 16 typically contains operating system 36, application programs 37, measuring device DLL 38 according to the invention, and other files and data. Operating system 36 includes printer driver 40 and measuring device driver 41. Measuring device driver 41 is one of plural different types of measuring device drivers corresponding to the type of measuring device 10 connected to computer system 6. Examples of measuring device driver 41 include XY table driver 43 for XY table 2, strip reader driver 44 for strip reader 3, patch reader driver 45 for hand-held patch reader 4, and scanner driver 46 for scanner 5. Some or all of these drivers can be stored on fixed disk 16.

Application programs 37 include color calibration program 48. The structure and operation of color calibration program 48 is explained in more detail below with reference to Figure 3.

Measuring device DLL 38 is a library of functions that are called by an application program so as to use any of plural different color measuring devices supported by the DLL. In order to write an application program that calls these functions, a software developer uses a measuring device API according to the invention, as explained below with reference to Figures 5 and 6.

Figure 3 is a block diagram for explaining a system for calibration of color fidelity of a color printer by a color calibration program according to the invention. In Figure 3, color calibration program 48 runs on computer system 6 and sends print data 51 for printing color patches to printer driver 40. The color patches are for use in calibration of color printer 1.

Color calibration program 48 makes API calls 52 to functions provided by measuring device

5
10
15
20
25
30

35

5 In response to print data 51 received from
color calibration program 48, printer driver 40
sends print job 57 to color printer 1. Likewise, in
response to color adjustment commands 55 received
from color calibration program 48, printer driver 40
sends printer commands 58 to color printer 1.

Measuring device DLL 38 provides a common interface between color calibration program 48 and plural different types of color measuring devices. As mentioned above, functions in measuring device DLL 38 are called by API calls 52 from color calibration program 48. The functions in measuring device DLL 38 make device driver calls 62 based on API calls 52 in order to operate measuring device 10. Device driver calls 62 are calls to a device driver corresponding to the type of color measuring device 10. For example, if measuring device 10 is an XY table, device driver calls 62 are calls to an XY table driver. In response to device driver calls 62, measuring device DLL 38 is provided with color measurements 64 by measuring device driver 41. Measuring device DLL 38 in turn provides color calibration program 48 with display values and flow control data 53 and color measurements 54. The flow control data preferably is based at least in part on device characteristics 65 received from measuring device driver 41. The structures of the functions in measuring device DLL 38 according to the invention are explained in more detail below with reference to Figures 4, 8 and 9, and the

operation of the functions is explained with reference to Figures 7A to 7C.

Measuring device driver 41 is a device driver corresponding to the type of measuring device 10. Measuring device driver 41 receives device driver calls 62 from the functions in measuring device DLL 38. In response to these call, measuring device driver 41 sends device commands 66 to measuring device 10, which provides color measurements 67 to measuring device driver 41. Color measurements 67 in turn are provided to measuring device DLL 38 as color measurements 64.

As mentioned above, measuring device 10 receives printed color patches 61 as input. Measuring device 10 makes color measurements 67 of printed color patches 61 in accordance with device commands 66 received from measuring device driver 41. Measurement device 10 provides color measurements 67 to measuring device driver 41.

Figure 4 is a block diagram for explaining functionality provided in the DLL and accessed from the application through the API.

Briefly, the measuring device DLL illustrated in Figure 4 is accessed through a measuring device API according to the invention. The API provides a common interface between an application program and plural different types of color measuring devices each having at least one color measuring sensor. The interface includes plural functions for operating any of the plural different types of color measuring devices. In order to complete an operation performed by one or more of the functions, the function that performs the operation must be called a number of times which is different for different types of color measuring devices. For a color measuring device that is being operated, the API provides the application program

with flow control data of the number of times that the function must be called. In Figure 4, this flow control data is provided for some of the functions by a separate get-device capabilities function.

5 This flow control data is provided for other functions by the functions themselves, in the form of "call-again" values provided by the functions to the color calibration program. The functions in the API also preferably provide the application program
10 with display values which are different for different types of color measuring devices. The values are displayed by the color calibration program to a user so as to instruct the user in manipulating the color measuring device that is
15 being operated.

In more detail, Figure 4 shows measuring device DLL 38 which is accessed by an application program through a measuring device API according to the invention. Thus, the API provides an interface
20 for a software developer to write an application program that calls the functions in the DLL illustrated in Figure 4. The functions provide an interface between color calibration program 48 and measuring device driver 41. Measuring device
25 driver 41 in turn communicates with measuring device 10 through measuring device interface 9.

Measuring device driver 41 is a device driver corresponding to the type of measuring device 10. Thus, brackets next to measuring device
30 driver 41 in Figure 4 indicate that measuring device driver 41 is one of plural different device drivers such as XY table driver 43, strip reader driver 44, patch reader driver 45, and scanner driver 46. Likewise, brackets next to measuring device 10 in
35 Figure 4 indicate that measuring device 10 is one of XY table 2, strip reader 3, hand-held patch reader 4 for reading individual color patches, and scanner 5.

It should be noted that the various drivers and devices shown in Figure 4 are only representative of the possible drivers and devices that can be operated using the API according to the invention.

In Figure 4, measuring device DLL 38 includes at least the following functions, which are provided to an application program through a measuring device API according to the invention:

get-device-capabilities 71, calibrate-position 72, calibrate-sensor 73, move-to-patch 74, and make measurement 75. Arrows pointing into blocks for these functions indicate information provided to the functions by color calibration program 48.

Likewise, arrows pointing out of blocks for these functions indicate information provided by the functions to color calibration program 48.

Information can be provided in various different ways to the functions by color calibration program 48 and by the functions to color calibration program 48. For example, information can be provided to a function as a passed variable, by modification of a shared (e.g., global) variable or data space, by passing a pointer to a memory location that stores the information, or through messages in a message-based environment. Likewise, information can be provided by a function as a returned value, by modification of a shared variable or data space, by modification of a memory location pointed to by a pointer, or through messages. Any or all of these methods, as well as any other additional methods, can be utilized by measuring device DLL 38 according to the invention.

Get-device-capabilities function 71 according to the invention provides color calibration program 48 with flow control data for calibrate-position function 72 and calibrate-sensor

5
10

15
20
25

30

35

calibration program 48 with number of calls 77 that must be made to calibrate-position function 72 in order to complete the position calibration operation. Number of calls 77 preferably is based at least in part on device characteristics 65.

Each time calibrate-position function 72 is called, the user might be required to perform a task such as positioning the sensor(s), positioning the recording medium, or otherwise manipulating measuring device 10. Calibrate-position function 72 preferably provides display values 80 to color calibration program 48, and program 48 displays display values 80 to a user so as to instruct the user to perform these tasks, as necessary.

Display values 80, as well as all other display values provided by measuring device DLL 38, can include text and/or graphics, or any other type of values displayable by computer system 6. Because the application program actually displays the display values, the application program can determine the form of the display. For example, the application program can display text or graphics based on the display values. The display values do not necessarily need to be displayed visually. For example, if the application program includes text-to-speech functionality, the program can generate speech based on the display values.

Calibrate-sensor function 73 is called to calibrate the sensor(s) of any of the plural different types of color measuring devices. In order to calibrate the sensor(s), calibrate-sensor function 73 might have to be called more than once. As discussed above, get-device-capabilities function 71 according to the invention provides color calibration program 48 with number of calls 78 that must be made to calibrate-sensor function 73 so as to complete the sensor calibration operation.

Number of calls 78 preferably is based at least in part on device characteristics 65.

Each time calibrate-sensor function 73 is called, the user might be required to perform a task such as manipulating measuring device 10. Calibrate-sensor function 73 preferably provides display values 82 to color calibration program 48 for display by the program to a user so as to instruct the user to perform any such tasks.

Move-to-patch function 74 is called to relatively position the sensor(s) and a color patch for any of the plural different types of color measuring devices. Move-to-patch function 74 is provided with logical color patch number 84 by color calibration program 48. In response, move-to-patch function 74 moves the sensor(s) or the recording medium so as to position the sensor(s) at the corresponding color patch, provides color calibration program 48 with display values 85 so as to instruct the user to move the sensor(s) or the recording medium, or both.

In order to relatively position the sensor(s) at the patch, move-to-patch function 74 might have to be called multiple times, depending on the type of measuring device 10. For example, if the color patch corresponding to color patch number 84 is on a next sheet or strip of recording medium, move-to-patch function 74 might have to be called a first time so as to instruct a user to change the sheet or strip, a second time so as to recalibrate the position of the recording medium (by providing a recalibrate value), and then a third time so as to move to the first patch on the recording medium. The number of times that move-to-patch function 74 needs to be called preferably is determined by the function based at least in part on device characteristics 65. If move-to-patch

function 74 needs to be called multiple times, move-to-patch function 74 provides color calibration program 48 with flow control data indicating whether the function has been called the necessary number of times. As shown in Figure 4, this flow control data takes the form of call-again value 86, which is provided if move-to-patch function 74 has not been called the necessary number of times.

In some situations, and in particular when a new recording medium is input to measuring device 10, the relative position of the recording medium and measuring device 10 might have to be recalibrated. Move-to-patch function 74 provides color calibration program 48 with recalibrate value 87 in such situations.

Make-measurement function 75 is called to make a color measurement of the patch at which the sensor(s) are relatively positioned. Make-measurement function 75 provides color calibration program 48 with color measurement 54 for the color patch. In addition, make-measurement function 75 preferably provides color calibration program 48 with display values 89 for display by the program to instruct the user to perform any necessary tasks for making the color measurement.

As with move-to-patch function 74, make-measurement function 75 might have to be called multiple times in order to complete its operation. The number of times that make-measurement function 75 needs to be called preferably is determined by the function based at least in part on device characteristics 65. If make-measurement function 75 needs to be called multiple times, make-measurement function 75 provides color calibration program 48 with flow control data indicating whether the function has been called the necessary number of times. As shown in Figure 4, this flow control data

takes the form of call-again value 90, which is provided if make-measurement function 75 has not been called the necessary number of times.

5 If the sensor(s) need to be recalibrated after a color measurement, for example after a certain number of color measurements, make-measurement function 75 provides color calibration program 48 with recalibrate value 91.

10 Figure 5 is a representational view of a development system for development of an application program using a measuring device API according to the invention. As shown in Figure 5, development system 100 is provided with display 102 which may be a color monitor, keyboard 104 for entering user
15 commands and for entering code for an application program, and pointing device 105 such as a mouse. Development system 100 also includes a mass storage device such as fixed disk 106. This mass storage device is for storing computer-executable process
20 steps for an operating system, software development programs, and a measuring device API according to the invention. Such storage may also be provided by a CD-ROM (not shown).

25 It should be understood that, although development system 100 is shown as a programmable general-purpose computer in Figure 5, a dedicated computer terminal or other type of data processing equipment can be used to write application programs utilizing the API according to the present
30 invention.

Figure 6 is a detailed block diagram showing the internal architecture of development system 100. As shown in Figure 6, development system 100 includes central processing unit 113
35 which interfaces with computer bus 114. Also interfacing with computer bus 114 are fixed disk 106, main memory (RAM) 116, read only memory

(ROM) 117, floppy disk interface 119, display interface 120 to display 102 (not shown), keyboard interface 122 to keyboard 104 (not shown), and pointing device interface 123 to pointing device 105 (not shown).

Main memory 116 interfaces with computer bus 114 so as to provide RAM storage to CPU 113 during execution of software applications. More specifically, CPU 113 loads process steps from fixed disk 106, another storage device, or some other source such as a network (not shown), into main memory 116. CPU 113 then executes the stored process steps from main memory 116 in order to execute application programs. Data such as code for an application program utilizing a measuring device API according to the invention can be stored in main memory 116, where the data can be accessed by CPU 113 during execution of the process steps.

As shown in Figure 6, fixed disk 106 typically contains operating system 126, application programs 127, and measuring device API 128 according to the invention. Operating system 126 typically is a windowing operating system and preferably is compatible with operating system 36 of computer system 6. Application programs 127 preferably includes software development programs 130 for developing application programs for making color measurements with color measuring devices.

A software developer uses software development programs 130 to write code for an application program such as color calibration program 48. The software developer includes calls to functions provided by measuring device API 128 in order to have the application program make color measurements with any color measuring device supported by the API.

The API preferably includes headers corresponding to the functions in measuring device DLL 38. When the software developer compiles the code for application program using software development programs 130, these headers allow the application program to access the functions in measuring device DLL 38. These functions provide a common interface to any of the plural supported color measuring devices. Therefore, as long as the application program includes code for handling flow control data and display values returned by the functions in the DLL, as described above with reference to Figures 3 and 4, the application program is able to make color measurements with any of the plural supported color measuring devices.

Figures 7A to 7C are flowcharts for explaining a representative color calibration application using a measuring device API according to the invention.

In step S701 in Figure 7A, color calibration program 48 generates print data 51 for color patches for calibration of color fidelity of color printer 1. In step S702, color calibration program 48 sends print data 51 to printer driver 40, which in turn sends print job 57 to color printer 1 based on print data 51. Color printer 1 prints the print job onto a recording medium, resulting in printed color patches 61.

In step S703, color calibration program 48 makes API call 52 to get-device-capabilities function 71 in measuring device DLL 38. In response, get-device-capabilities function 71 provides flow control data to calibration program 48. This flow control data preferably includes number of calls 77 and number of calls 78, which indicate the number of times calibrate-position function 71 and calibrate-sensor function

72 need to be called in order to perform their respective operations.

5 In step S704, the relative position of the sensor(s) with respect to the recording medium is calibrated. Figure 7B is a flowchart for explaining position calibration according to the invention.

10 In step S705 of Figure 7B, color calibration program 48 calls calibrate-position function 72. This function sends device driver calls 62 to measuring device driver 41, which in turn sends device commands 66 to measuring device 10 so as to calibrate the relative position of the sensor(s).

15 In step S706, color calibration program 48 determines if calibrate-position function 72 provided display values 80. If calibrate-position function 72 did provide display values 80, color calibration program 48 displays the display values to the user, such as on display 12, in step S707.

20 In step S708, color calibration program 48 determines if calibrate-position function 72 has been called the number of times indicated by number of calls 77. If calibrate-position function 72 has not been called number of calls 77 times, flow returns to step S705. Once calibrate-position function 72 has been called number of calls 77 times, flow returns to Figure 7A.

25 In Figure 7A, flow proceeds to step S709, where the sensor(s) are calibrated. Figure 7C is a flowchart for explaining sensor calibration according to the invention.

30 In step S710 of Figure 7C, color calibration program 48 calls calibrate-sensor function 72. This function sends device driver calls 62 to measuring device driver 41, which in turn sends device commands 66 to measuring device 10 so as to calibrate the sensor(s).

5

10

15

20

25

35

recording medium. For example, hand-held patch reader 4 has no mechanism for moving its sensor(s) or a recording medium. Rather, the user must move the sensor(s) or the recording medium. In that case, display values 85 sent in step S716 instructs the user to perform this task, as necessary.

In step S717, color calibration program 48 determines if move-to-patch function 74 has indicated that position of the recording medium needs to be recalibrated. If the position does need to be recalibrated, flow proceeds to step S718, where the position is recalibrated as explained above with reference to Figure 7B.

Flow proceeds to step S719, where color calibration program 48 determines if move-to-patch function 74 needs to be called again so as to complete positioning of the sensor(s). Color calibration program 48 makes this determination by checking for flow control data from move-to-patch function 74 in the form of call-again value 86. If move-to-patch function 74 needs to be called again, flow returns to step S714. Otherwise, flow proceeds to step S720.

In step S720, color calibration program 48 calls make-measurement function 75. This function sends device driver calls 62 to measuring device driver 41, which in turn uses device commands 66 to instruct measuring device 10 to make a color measurement. Once the measuring operation is complete, measuring device 10 generates color measurement 67 based on this measuring operation and sends color measurement 67 to measuring device driver 41. Measuring device driver 41 sends this color measurement to make-measurement function 75 in measuring device DLL 38 in the form of color measurement 64, and the make-measurement function

provides the measurement to color calibration program 48 as color measurement 54.

5 In step S721, color calibration program 48 determines if make-measurement function 75 provided display values 89 to the program. If make-measurement function 75 did provide display values 89, color calibration program 48 displays the display values to the user in step S722.

10 In step S723, color calibration program 48 determines if make-measurement function 75 has indicated that the sensor(s) need to be recalibrated. If the sensor(s) do need to be recalibrated, flow proceeds to step S724, where the sensor(s) are recalibrated as explained above with
15 reference to Figure 7C.

Flow proceeds to step S725, where color calibration program 48 determines if make-measurement function 75 needs to be called again so as to complete making the color measurement. Color
20 calibration program 48 makes this determination by checking for flow control data from make-measurement function 74 in the form of call-again value 90. If make-measurement function 75 needs to be called again, flow returns to step S720. Otherwise, flow
25 proceeds to step S726.

In step S726, color calibration program 48 determines if all color patches for calibrating color printer 1 have been measured. If more color patches need to be measured, flow returns to step
30 S714. Otherwise, flow proceeds to step S727.

In step S727, color calibration program 48 generates color adjustment commands 55 based at least in part on color measurements 54. Color calibration program 48 sends these commands to
35 printer driver 40, which in turn sends print commands 58 to color printer 1 so as to adjust the color fidelity of the printer.

Because each of the functions in measuring device DLL 38 accessed through measuring device API 128 makes device driver calls 62 to measuring device 41 for the type of color measuring device 10, color calibration program 48 is insulated from the differences between different types of color measuring devices. Furthermore, the flow control data for multiple calls provided to color calibration program 48 allows the program to call the functions the necessary number of times for each operation without knowing the type of the actual device. The display values provided to the program allow the program to display the display values appropriate for the type of measuring device 10 that is being used. Moreover, since the application program generates displays based on the display values rather than the DLL, the application program can package a message however it wants so as to permit each developer to give his application a unique and internally-consistent GUI. As a result, a block of code that accesses color measuring device DLL 38 can make color measurements with any type of color measuring device supported by the API, despite the different device driver commands needed to calibrate and operate the different types of devices.

Included in a microfiche appendix submitted herewith is sample code that operates generally as described above. This code includes code for a portion of a color calibration program that makes color measurements using an API according to the invention, the API itself, and a DLL accessed through the API. This code is provided for illustrative purposes only. Other implementations of the color measurement code, measuring device API, and measuring device DLL exist that are within the scope and spirit of the invention.

Figure 8 is a block diagram for explaining a variation of the structure of the measuring device DLL according to the invention and of the API used to access the DLL. As shown in Figure 8, both
5 calibrate-position function 72 and calibrate-sensor function 73 can provide call-again values 140 and 141, respectively, to color calibration program 48. These call-again values are provided by these functions when they need to be called more
10 than once in order to complete their respective operations.

Because the calibration functions can return these call-again values to facilitate multiple calls, there is no need for get-device-
15 capabilities function 71 to provide number of calls 77 and number of calls 78 to the calibration functions. Of course, get-device-capabilities function 71 can still be included in the API, if desired.

Figure 9 is a block diagram for explaining another variation of the structure of the measuring device API according to the invention. In this variation, each of the functions in the API provides flow control data in the form of a "number of calls"
20 value to indicate how many times that function should be called in order to complete its respective operation. Thus, calibrate-position function 72 provides number of calls 143, calibrate-sensor function 73 provides number of calls 154, move-to-
25 patch function 74 provides number of calls 155, and make-measurement function 75 provides number of calls 156. These values can be a total number of calls that need to be made to each function. For example, if three calls need to be made to
30 calibrate-position function 72, then that function would provide a value of "three" each time it was called. Alternatively, each function can maintain
35

5
10

15

20

WHAT IS CLAIMED IS:

1. Computer-executable process steps to provide an application programming interface (API), the application programming interface providing a common interface between an application program and plural different types of color measuring devices each having at least one color measuring sensor, the computer-executable process steps comprising plural functions for operating any of the plural different types of color measuring devices, wherein in order to complete an operation performed by at least one of the plural functions, the function that performs the operation must be called a number of times which is different for at least two different types of color measuring devices, and wherein for a color measuring device that is being operated, the API provides the application program with flow control data of the number of times that the function must be called.

2. Computer-executable process steps according to Claim 1, wherein the flow control data is provided by the function which must be called the number of times in order to complete the operation.

3. Computer-executable process steps according to Claim 2, wherein the flow control data is provided in the form of a call-again value.

4. Computer-executable process steps according to Claim 2, wherein the flow control data is provided in the form of a numerical value.

5. Computer-executable process steps according to Claim 1, wherein the flow control data is provided by a separate function other than the

function which must be called the number of times in order to complete the operation.

5 6. Computer-executable process steps
according to Claim 1, wherein functions in the API
provide the application program with display values
which are different for at least two different types
of color measuring devices, the display values for
display to a user so as to instruct the user in
10 manipulating the color measuring device that is
being operated.

15 7. Computer-executable process steps
according to Claim 6, wherein the plural functions
for operating any of the plural different types of
color measuring devices further comprise:
 a calibrate-position function to calibrate
a relative position of a recording medium with
respect to any of the plural different types of
20 color measuring devices;
 a calibrate-sensor function to calibrate
any of the color measuring sensors of any of the
plural different types of color measuring devices;
 a move-to-patch function to relatively
25 position any of the color measuring sensors and a
color patch for any of the plural different types of
color measuring devices, the move-to-patch function
being provided with a logical color patch number by
the application program; and
30 a make-measurement function to make a color
measurement of the patch at which any of the color
measuring sensors is relatively positioned, the
make-measurement function providing the application
program with a color measurement value for the color
35 patch.

8. Computer-executable process steps to provide an application programming interface (API), the API providing a common interface between an application program and plural different types of color measuring devices each having at least one color measuring sensor, the computer-executable process steps comprising plural functions for operating any of the plural different types of color measuring devices, the plural functions comprising:

a calibrate-position function to calibrate a relative position of a recording medium with respect to any of the plural different types of color measuring devices;

a calibrate-sensor function to calibrate any of the color measuring sensors of any of the plural different types of color measuring devices;

a move-to-patch function to relatively position any of the color measuring sensors and a color patch for any of the plural different types of color measuring devices, the move-to-patch function being provided with a logical color patch number by the application program; and

a make-measurement function to make a color measurement of the patch at which any of the color measuring sensors is relatively positioned, the make-measurement function providing the application program with a color measurement value for the color patch;

wherein in order to complete an operation performed by at least one of the plural functions, the function that performs the operation must be called a number of times which is different for at least two different types of color measuring devices, and wherein for a color measuring device that is being operated, the API provides the application program with flow control data of the number of times that the function must be called.

9. Computer-executable process steps
according to Claim 8, wherein the calibrate-position
function provides the application program with at
least one display value that is to be displayed so
as to instruct a user to position the recording
medium or to position any of the color measuring
sensors.

10. Computer-executable process steps
according to Claim 8, wherein the calibrate-sensor
function provides the application program with at
least one display value that is to be displayed so
as to instruct the user in calibrating the sensor.

11. Computer-executable process steps
according to Claim 8, wherein the move-to-patch
function causes the color measuring device to move
any of the color measuring sensors so as to
relatively position any of the color measuring
sensors and the color patch.

12. Computer-executable process steps
according to Claim 8, wherein the move-to-patch
function provides the application program with at
least one display value that is to be displayed so
as to instruct the user to manipulate any of the
color measuring devices so as to relatively position
any of the color measuring sensors and the color
patch.

13. Computer-executable process steps
according to Claim 8, wherein the move-to-patch
function causes the color measuring device to move
the recording medium so as to relatively position
any of the color measuring sensors and the color
patch.

5

10

15

25

30

35

5

10

15

20

25

30

35

27. Computer-executable process steps to provide an application programming interface (API), the API providing a common interface between an

application program and plural different types of color measuring devices each having at least one color measuring sensor, the computer-executable process steps comprising plural functions for operating any of the plural different types of color measuring devices, the plural functions comprising:

a calibrate-position function to calibrate a relative position of a recording medium with respect to any of the plural different types of color measuring devices, the calibrate-position function providing the application program with a position-calibration display value that is to be displayed so as to instruct a user to position the recording medium or to position any of the color measuring sensors;

a calibrate-sensor function to calibrate any of the color measuring sensors of any of the plural different types of color measuring devices, the calibrate-sensor function providing the application program with a sensor-calibration display value to the application program, the sensor-calibration display value to be displayed so as to instruct the user in calibrating any of the color measuring sensors;

a move-to-patch function to relatively position any of the color measuring sensors and a color patch for any of the plural different types of color measuring devices, the move-to-patch function being provided with a logical color patch number by the application program, providing the application program with a call-again value in a case that the move-to-patch function needs to be called multiple times to complete the relative positioning of the color measuring sensors and has not yet been called the multiple times, and providing the application program with a move-to-patch display value that is

to be displayed so as to instruct the user in
positioning any of the color measuring sensors; and
a make-measurement function to make a color
measurement of the patch at which any of the color
measuring sensors is relatively positioned, the
make-measurement function providing the application
program with a color measurement value for the color
patch, providing the application program with a
call-again value in a case that the make-measurement
function needs to be called multiple times to
complete making the color measurement of the color
patch and has not yet been called the multiple
times, and providing the application program with a
measurement display value that is to be displayed so
as to instruct the user in making the color
measurement.

28. Computer-executable process steps
according to Claim 27, further comprising a get-
device-capabilities function to provide the
application program with a number of times that the
calibrate-position function needs to be called so as
to calibrate the relative position of the recording
medium and to provide the application program with a
number of times that the calibrate-sensor function
needs to be called so as to calibrate any of the
color measuring sensors.

29. Computer-executable process steps
according to Claim 27, wherein the calibrate-
position function further provides the application
program with a number of times that the calibrate-
position function needs to be called so as to
calibrate the relative position of the recording
medium.

30. Computer-executable process steps according to Claim 27, wherein the calibrate-position function further provides the application program with a call-again value in a case that the calibrate-position function needs to be called multiple times so as to calibrate the relative position of the recording medium and has not yet been called the multiple times.

31. Computer-executable process steps according to Claim 27, wherein the calibrate-sensor function further provides the application program with a number of times that the calibrate-sensor function needs to be called so as to calibrate any of the color measuring sensors.

32. Computer-executable process steps according to Claim 27, wherein the calibrate-sensor function further provides the application program with a call-again value in a case that the calibrate-sensor function needs to be called multiple times so as to calibrate any of the color measuring sensors and has not yet been called the multiple times.

33. Computer-executable process steps according to Claim 27, wherein the move-to-patch function causes the color measuring device to move the sensor so as to relatively position any of the color measuring sensors and the color patch.

34. Computer-executable process steps according to Claim 27, wherein the move-to-patch display value instructs the user to manipulate any of the color measuring devices so as to relatively position any of the color measuring sensors and the color patch.

35. Computer-executable process steps
according to Claim 27, wherein the move-to-patch
function causes any of the color measuring devices
to manipulate any of the color measuring devices so
as to relatively position any of the color measuring
sensors and the color patch.

36. Computer-executable process steps
according to Claim 27, wherein the move-to-patch
display value instructs the user to manipulate any
of the color measuring devices so as to relatively
position any of the color measuring sensors and the
color patch.

37. Computer-executable process steps
according to Claim 27, wherein the move-to-patch
function further provides the application program
with a recalibrate value in a case that the relative
position of the recording medium needs to be
recalibrated.

38. Computer-executable process steps
according to Claim 27, wherein the make-measurement
function further provides the application program
with a recalibrate value in a case that any of the
color measuring sensors needs to be recalibrated.

39. Computer-executable process steps
according to Claim 27, wherein functions in the API
call device driver function for the different types
of color measuring devices.

40. Computer-executable process steps
according to Claim 27, wherein the computer-
executable process steps are stored in a dynamically
linkable library.

41. Computer-executable process steps according to Claim 27, wherein the plural different types of color measuring devices include XY tables and hand-held patch readers.

5

42. Computer-executable process steps according to Claim 27, wherein the plural different types of color measuring devices include spectrometers and densitometers.

10

43. Computer-executable process steps according to Claim 27, wherein the application program is a color calibration program.

15

44. A dynamically linkable library (DLL) for making color measurements with any of plural different types of color measuring devices each having at least one color measuring sensor, the DLL comprising plural functions each of which is for operating any of the plural different types of color measuring devices, the plural functions comprising:

20

a calibrate-position function to calibrate a relative position of a recording medium with respect to any of the plural different types of color measuring devices;

25

a calibrate-sensor function to calibrate any of the color measuring sensors of any of the plural different types of color measuring devices;

30

a move-to-patch function to relatively position any of the color measuring sensors and a color patch for any of the plural different types of color measuring devices, the move-to-patch function being provided with a logical color patch number; and

35

a make-measurement function to make a color measurement of the patch at which any of the color measuring sensors is relatively positioned, the

66000-2347460

make-measurement function providing a color measurement value for the color patch;

5 wherein in order to complete an operation performed by at least one of the plural functions, the function that performs the operation must be called a number of times which is different for at least two different types of color measuring devices, and wherein for a color measuring device that is being operated, the DLL provides flow control data of the number of times that the function must be called.

15 45. A color calibration program, the color calibration program comprising computer-executable process steps to calibrate color fidelity of a color printer based on color measurements made by a color measuring device of color patches printed on a recording medium by the color printer, the computer-executable process steps comprising:

20 code to generate print data for the color patches;

code to send the print data to the color printer so as to print the color patches on the recording medium;

25 code to make color measurements of the color patches printed on the recording medium using any of plural different types of color measuring devices, the code to make color measurements calling functions provided by an application programming interface (API) that provides a common interface to the plural different types of color measuring devices, the code to make color measurements using the common interface; and

30 code to calibrate the color fidelity of the color printer based on the color measurements.

662020-2581400

46. A computer-readable medium which stores computer-executable process steps, the computer-executable process steps to provide an application programming interface (API), the application programming interface providing a common interface between an application program and plural different types of color measuring devices each having at least one color measuring sensor, the computer-executable process steps comprising plural functions for operating any of the plural different types of color measuring devices, wherein in order to complete an operation performed by at least one of the plural functions, the function that performs the operation must be called a number of times which is different for at least two different types of color measuring devices, and wherein for a color measuring device that is being operated, the API provides the application program with flow control data of the number of times that the function must be called.

47. A computer-readable medium according to Claim 46, wherein the flow control data is provided by the function which must be called the number of times in order to complete the operation.

48. A computer-readable medium according to Claim 47, wherein the flow control data is provided in the form of a call-again value.

49. A computer-readable medium according to Claim 47, wherein the flow control data is provided in the form of a numerical value.

50. A computer-readable medium according to Claim 46, wherein the flow control data is provided by a separate function other than the

function which must be called the number of times in order to complete the operation.

5 51. A computer-readable medium according
to Claim 46, wherein functions in the API provide
the application program with display values which
are different for at least two different types of
color measuring devices, the display values for
display to a user so as to instruct the user in
10 manipulating the color measuring device that is
being operated.

15 52. A computer readable medium according
to Claim 51, wherein the plural functions for
operating any of the plural different types of color
measuring devices further comprise:

20 a calibrate-position function to calibrate
a relative position of a recording medium with
respect to any of the plural different types of
color measuring devices;

a calibrate-sensor function to calibrate
any of the color measuring sensors of any of the
plural different types of color measuring devices;

25 a move-to-patch function to relatively
position any of the color measuring sensors and a
color patch for any of the plural different types of
color measuring devices, the move-to-patch function
being provided with a logical color patch number by
the application program; and

30 a make-measurement function to make a color
measurement of the patch at which any of the color
measuring sensors is relatively positioned, the
make-measurement function providing the application
program with a color measurement value for the color
35 patch.

53. A computer readable medium storing computer-executable process steps, the computer-executable process steps to provide an application programming interface (API), the API providing a common interface between an application program and plural different types of color measuring devices each having at least one color measuring sensor, the computer-executable process steps comprising plural functions for operating any of the plural different types of color measuring devices, the plural functions comprising:

a calibrate-position function to calibrate a relative position of a recording medium with respect to any of the plural different types of color measuring devices;

a calibrate-sensor function to calibrate any of the color measuring sensors of any of the plural different types of color measuring devices;

a move-to-patch function to relatively position any of the color measuring sensors and a color patch for any of the plural different types of color measuring devices, the move-to-patch function being provided with a logical color patch number by the application program; and

a make-measurement function to make a color measurement of the patch at which any of the color measuring sensors is relatively positioned, the make-measurement function providing the application program with a color measurement value for the color patch;

wherein in order to complete an operation performed by at least one of the plural functions, the function that performs the operation must be called a number of times which is different for at least two different types of color measuring devices, and wherein for a color measuring device that is being operated, the API provides the

application program with flow control data of the number of times that the function must be called.

5 54. A computer-readable medium according to Claim 53, wherein the calibrate-position function provides the application program with at least one display value that is to be displayed so as to instruct a user to position the recording medium or to position any of the color measuring sensors.

10 55. A computer-readable medium according to Claim 53, wherein the calibrate-sensor function provides the application program with at least one display value that is to be displayed so as to
15 instruct the user in calibrating the sensor.

20 56. A computer-readable medium according to Claim 53, wherein the move-to-patch function causes the color measuring device to move any of the color measuring sensors so as to relatively position any of the color measuring sensors and the color patch.

25 57. A computer-readable medium according to Claim 53, wherein the move-to-patch function provides the application program with at least one display value that is to be displayed so as to instruct the user to manipulate any of the color measuring devices so as to relatively position any
30 of the color measuring sensors and the color patch.

35 58. A computer-readable medium according to Claim 53, wherein the move-to-patch function causes the color measuring device to move the recording medium so as to relatively position any of the color measuring sensors and the color patch.

59. A computer-readable medium according
to Claim 53, wherein the move-to-patch function
provides the application program with at least one
display value that is to be displayed so as to
5 instruct the user to move the recording medium so as
to relatively position any of the color measuring
sensors and the color patch.

60. A computer-readable medium according
10 to Claim 53, wherein the move-to-patch function
provides the application program with a recalibrate
value in a case that the relative position of the
recording medium needs to be recalibrated.

61. A computer readable medium according
15 to Claim 53, wherein the make-measurement function
provides the application program with at least one
display value that is to be displayed so as to
instruct the user in making the color measurement.

62. A computer-readable medium according
20 to Claim 53, wherein the make-measurement function
further provides the application program with a
recalibrate value in a case that any of the color
measuring sensors needs to be recalibrated.

63. A computer readable medium according
to Claim 53, wherein the flow control data is
provided by the function which must be called the
30 number of times in order to complete the operation.

64. A computer readable medium according
to Claim 63, wherein the flow control data is
provided in the form of a call-again value.

5 66. A computer-readable medium according
to Claim 53, wherein the plural functions further
comprise a get-device-capabilities function to
provide the application program with the flow
control data.

15 68. A computer-readable medium according
to Claim 53, wherein the computer-executable process
steps are stored in a dynamically linkable library.

25 70. A computer-readable medium according
to Claim 53, wherein the plural different types of
color measuring devices include spectrometers and
densitometers.

35 72. A computer-readable medium storing
computer-executable process steps, the computer-
executable process steps to provide an application
programming interface (API), the API providing a

common interface between an application program and plural different types of color measuring devices each having at least one color measuring sensor, the computer-executable process steps comprising plural functions for operating any of the plural different types of color measuring devices, the plural functions comprising:

a calibrate-position function to calibrate a relative position of a recording medium with respect to any of the plural different types of color measuring devices, the calibrate-position function providing the application program with a position-calibration display value that is to be displayed so as to instruct a user to position the recording medium or to position any of the color measuring sensors;

a calibrate-sensor function to calibrate any of the color measuring sensors of any of the plural different types of color measuring devices, the calibrate-sensor function providing the application program with a sensor-calibration display value to the application program, the sensor-calibration display value to be displayed so as to instruct the user in calibrating any of the color measuring sensors;

a move-to-patch function to relatively position any of the color measuring sensors and a color patch for any of the plural different types of color measuring devices, the move-to-patch function being provided with a logical color patch number by the application program, providing the application program with a call-again value in a case that the move-to-patch function needs to be called multiple times to complete the relative positioning of the color measuring sensors and has not yet been called the multiple times, and providing the application program with a move-to-patch display value that is

to be displayed so as to instruct the user in
positioning any of the color measuring sensors; and
a make-measurement function to make a color
measurement of the patch at which any of the color
measuring sensors is relatively positioned, the
make-measurement function providing the application
program with a color measurement value for the color
patch, providing the application program with a
call-again value in a case that the make-measurement
function needs to be called multiple times to
complete making the color measurement of the color
patch and has not yet been called the multiple
times, and providing the application program with a
measurement display value that is to be displayed so
as to instruct the user in making the color
measurement.

73. A computer-readable medium according
to Claim 72, further comprising a get-device-
capabilities function to provide the application
program with a number of times that the calibrate-
position function needs to be called so as to
calibrate the relative position of the recording
medium and to provide the application program with a
number of times that the calibrate-sensor function
needs to be called so as to calibrate any of the
color measuring sensors.

74. A computer-readable medium according
to Claim 72, wherein the calibrate-position function
further provides the application program with a
number of times that the calibrate-position function
needs to be called so as to calibrate the relative
position of the recording medium.

75. A computer-readable medium according
to Claim 72, wherein the calibrate-position function

further provides the application program with a call-again value in a case that the calibrate-position function needs to be called multiple times so as to calibrate the relative position of the recording medium and has not yet been called the multiple times.

76. A computer-readable medium according to Claim 72, wherein the calibrate-sensor function further provides the application program with a number of times that the calibrate-sensor function needs to be called so as to calibrate any of the color measuring sensors.

77. A computer-readable medium according to Claim 72, wherein the calibrate-sensor function further provides the application program with a call-again value in a case that the calibrate-sensor function needs to be called multiple times so as to calibrate any of the color measuring sensors and has not yet been called the multiple times.

78. A computer-readable medium according to Claim 72, wherein the move-to-patch function causes the color measuring device to move the sensor so as to relatively position any of the color measuring sensors and the color patch.

79. A computer-readable medium according to Claim 72, wherein the move-to-patch display value instructs the user to manipulate any of the color measuring devices so as to relatively position any of the color measuring sensors and the color patch.

80. A computer-readable medium according to Claim 72, wherein the move-to-patch function causes any of the color measuring devices to

manipulate any of the color measuring devices so as to relatively position any of the color measuring sensors and the color patch.

5 81. A computer-readable medium according to Claim 72, wherein the move-to-patch display value instructs the user to manipulate any of the color measuring devices so as to relatively position any of the color measuring sensors and the color patch.

10 82. A computer-readable medium according to Claim 72, wherein the move-to-patch function further provides the application program with a recalibrate value in a case that the relative
15 position of the recording medium needs to be recalibrated.

20 83. A computer-readable medium according to Claim 72, wherein the make-measurement function further provides the application program with a recalibrate value in a case that any of the color measuring sensors needs to be recalibrated.

25 84. A computer-readable medium according to Claim 72, wherein functions in the API call device driver function for the different types of color measuring devices.

30 85. A computer-readable medium according to Claim 72, wherein the computer-executable process steps are stored in a dynamically linkable library.

35 86. A computer-readable medium according to Claim 72, wherein the plural different types of color measuring devices include XY tables and hand-held patch readers.

87. A computer-readable medium according to Claim 72, wherein the plural different types of color measuring devices include spectrometers and densitometers.

5

88. A computer-readable medium according to Claim 72, wherein the application program is a color calibration program.

10

89. A computer-readable medium storing a dynamically linkable library (DLL), the DLL for making color measurements with any of plural different types of color measuring devices each having at least one color measuring sensor, the DLL comprising plural functions each of which is for operating any of the plural different types of color measuring devices, the plural functions comprising:

15

a calibrate-position function to calibrate a relative position of a recording medium with respect to any of the plural different types of color measuring devices;

20

a calibrate-sensor function to calibrate any of the color measuring sensors of any of the plural different types of color measuring devices;

25

a move-to-patch function to relatively position any of the color measuring sensors and a color patch for any of the plural different types of color measuring devices, the move-to-patch function being provided with a logical color patch number; and

30

a make-measurement function to make a color measurement of the patch at which any of the color measuring sensors is relatively positioned, the make-measurement function providing a color measurement value for the color patch;

35

wherein in order to complete an operation performed by at least one of the plural functions,

662000-347450

the function that performs the operation must be called a number of times which is different for at least two different types of color measuring devices, and wherein for a color measuring device that is being operated, the DLL provides flow control data of the number of times that the function must be called.

90. A computer-readable medium storing a color calibration program, the color calibration program comprising computer-executable process steps to calibrate color fidelity of a color printer based on color measurements made by a color measuring device of color patches printed on a recording medium by the color printer, the computer-executable process steps comprising:

code to generate print data for the color patches;

code to send the print data to the color printer so as to print the color patches on the recording medium;

code to make color measurements of the color patches printed on the recording medium using any of plural different types of color measuring devices, the code to make color measurements calling functions provided by an application programming interface (API) that provides a common interface to the plural different types of color measuring devices, the code to make color measurements using the common interface; and

code to calibrate the color fidelity of the color printer based on the color measurements.

ABSTRACT OF THE DISCLOSURE

An application programming interface (API) that provides a common interface between an application program and plural different types of color measuring devices each having at least one color measuring sensor. The API includes plural functions for operating any of the plural different types of color measuring devices. In order to complete an operation performed by at least one of the plural functions, the function that performs the operation must be called a number of times which is different for at least two different types of color measuring devices. For a particular color measuring device, the API provides the application program with flow control data of the number of times that the function must be called. This flow control data preferably can be provided by the function, in the form of a call-again value or as a numerical value, or by a separate function in the API such as a get-device-capabilities function. In some embodiments of the invention, a combination of these methods of providing the flow control data is utilized. Preferred functions for operating any of the plural different types of color measuring devices include a calibrate-position function, a calibrate-sensor function, a move-to-patch function, and a make-measurement function.




FIG. 1




FIG. 2




FIG. 3




FIG. 5







FIG. 6








FIG. 8




FIG. 9

COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION

(Page 1)

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name:

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

APPLICATION PROGRAMMING INTERFACE FOR MEASURING DEVICES

the specification of which ☒ is attached hereto ☐ was filed on _____ as
United States Application No. or PCT International Application No. _____
and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. §119(a)-(d) or §365(b), of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT international application which designates at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed:

<u>Country</u>	<u>Application No.</u>	<u>Filed (Day/Mo./Yr.)</u>	<u>(Yes/No)</u> <u>Priority Claimed</u>
----------------	------------------------	----------------------------	--

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below:

<u>Application No.</u>	<u>Filed (Day/Mo./Yr.)</u>
------------------------	----------------------------

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

<u>Application No.</u>	<u>Filed (Day/Mo./Yr.)</u>	<u>Status</u> <u>(Granted, Pending, Abandoned)</u>
------------------------	----------------------------	---

004483-02000

**COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION
(Page 2)**

I hereby appoint the practitioners associated with the firm and Customer Number provided below to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to the address associated with that Customer Number:

FITZPATRICK, CELLA, HARPER & SCINTO
Customer Number: 05514

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or First Inventor Timothy L. Kohler

Inventor's signature *Timothy L. Kohler*

Date 2/2/99 Citizen/Subject of U.S.A.

Residence 910 Nevada Avenue, San Jose, CA 95125

Post Office Address c/o Canon Information Systems, Inc.

110 Innovation Drive, Irvine, CA 92612

Full Name of Second Joint Inventor, if any Todd Newman

Second Inventor's signature *Todd Newman*

Date 2/2/99 Citizen/Subject of U.S.A.

Residence 751 Marion Avenue, Palo Alto, CA 94303

Post Office Address c/o Canon Information Systems, Inc.

110 Innovation Drive, Irvine, CA 92612

Full Name of Third Joint Inventor, if any _____

Third Inventor's signature _____

Date _____ Citizen/Subject of _____

Residence _____

Post Office Address _____

Full Name of Fourth Joint Inventor, if any _____

Fourth Inventor's signature _____

Date _____ Citizen/Subject of _____

Residence _____

Post Office Address _____